



微图视觉
Vision Datum


VISION DATUM

Light Controller




Model	Drive Mode	Input Voltage	Output Voltage	Power	Output Current	Channel	Output Port	Adapt to line light
Digital Controller								
VT-LT4-0506PWDC-2	Constant Current	88V-264V	5V	Total:6W/Single :3W Expandable: Total:12W/Single:6W	/	2	SMP-03V	
VT-LT4-2420PWDC-2	Constant Voltage	88V-264V	24V	Total:20W Single:20W	/	2	SMP-03V	
VT-LT4-2460PWDC-4	Constant Voltage	88V-264V	24V	Total:60W Single:25W	/	4	SMP-03V	
VT-LT4-24150PWDC-4	Constant Voltage	88V-264V	24V	Total:150W Single:70W	/	4	SMP-03V	
VT-LT3-24240PWDC-2	Constant Current	100V-120V(Ver.A) 200V-240V(Ver.B)	24V	240W	Total:10A Single:10A	2	19M-5	√
VT-LT3-24500PWDC-2	Constant Voltage	100V-240V	24V	480W	Total:20A Single:light 9A, fan 1A	2	19M-2E	
VT-LT4-48300PWDC-1	Constant Current	90V-264V	48V	300W	0-6A	1	-	
Stroboscopic Controller (With Brightening Module)								
VT-LT3-PLU24120-4	Constant Voltage	100V-240V	48V	120W	10A (Instantaneous Value)	4	SMP-03V-BC	
VT-LT3-PLU24200-2	Constant Voltage	100V-240V	48V	200W	50A (Instantaneous Value)	2	12M-2	
VT-LT3-PLU24200-4	Constant Voltage	100V-240V	48V	200W	25A (Instantaneous Value)	4	SMP-03V-BC	
Line Source Stroboscopic Controller (With Brightening Module)								
VT-LT3-PLU481000LI-6	Constant Voltage	100V-240V	48V	1000W	Total:25A Single:25A	6	16M-2	√
line Source Controller								
VT-LT3-24300PWLI-1	Constant Voltage	100V-240V	24V	≤ 300W	12.5A	1	AM20K4Z	√
VT-LT3-48600PWLI-2	Constant Current	100V-120V(Ver.A) 200V-240V(Ver.B)	48V	600W	Total:12A Single:6A	2	19M-6	√
VT-LT3-48300PWLIN-2	Constant Current	100V-240V	48V	≤ 300W	Total:6A Single:6A	2	16M-6	√
VT-LT3-48600PWLIN-1	Constant Current	100V-120V(Ver.A) 180V-240V(Ver.B)	48V	≤ 600W	Total:12A Single:6A	1	19M-6	√
VT-LT3-48600PWLIN-2	Constant Current	180V-240V	48V	≤ 600W	Total:12A Single:6A	2	19M-6	√
VT-LT3-48800PWLIN-1	Constant Current	100-240V	48V	< 800W	14A	1	19M-6	√
VT-LT3-48800PWLIN-2	Constant Current	100-240V	48V	Total: ≤ 800W Single: ≤ 400W	14A	2	19M-6	√
VT-LT3-481200PWLIN-1	Constant Current	100V-240V	48V	≤ 1200W	Total:24A Single:12A	1	19M-6	√
Analog Controller								
VT-LT4-0506PWAC-2	Constant Current	88-264	5V	Total:6W Single:3W	/	2	SMP-03V	
VT-LT3-2460PWAC-4	Constant Voltage	100-240	24V	60W	Total:2.5A Single:2.5A	4	SMP-03V-BC	

PS: *Default -Ver.B version voltage



Line illumination
Li/ LiN+/LiC /MLi Series
 Bar illumination
HL/HL+/HLDM Series



Ring illumination
HR /HR+/LR Series
 Coaxial illumination
C/CP/CX Series



Bottom Flat Backlights illumination
BF/BFP Series
 Side Flat Backlights illumination
BFC/BFCP/BFCK Series



Shadowless Ring illumination
WR/LWR/GWR Series
 Shadowless Square illumination
MT Series



Dome illumination
DM Series
 Tunnel shadowless illumination
T Series



Spot illumination
PI Series
 Three-color illumination
AOI Series



Spot illumination
PI Series
 Fiber LED Lights Source Unit
CO Series



Telecentric illumination
CLW-LIT Series
 UV/IR/Waterproof/Corrosion
 Resistant illumination

More OEM/ODM Led illumination available, and please contact your sales engineer for projects confirmation.

Vision And More Available

让工业更智能，让视觉更简单！



SWIR Camera
Industrial Camera



Macro Lens
Industrial Lens



Microscope



System Solution
No-programming Software



ADD: No 8, Xiyuan 9th Road Hangzhou 310030 China
TEL: 86-571-86888309
Email: market@visiondatum.com
Web: www.visiondatum.com



Official Website



Online Store

Ver.23.2